



Seat and Back

Injection molded pure virgin polypropylene seat and slotted back. The one-piece construction of the seat and back provide a supportive flexing motion when seated with no mechanisms. Back is curved for lumbar support. The polypropylene shell is 17.5mm thick at the slotted area of the one piece shell. Shell is secured to steel frame with metal inserts and 4 bolts.

Optional Upholstery

Foam is .5" thick, 1.8# with a 60ILD density. Foam is attached to polypropylene backer then upholstery is stapled to backer. Upholstered seat pan is secured on top of polypropylene shell and secured with screws.

Frames

Legs are 12-gauge .75" round tubed steel. Cross braces are 12-gauge .75" round tubed steel and welded to legs using CO2 welding joints. Frame is secured to shell with 4 bolts that fasten into metal inserts on polypropylene shell. A polypropylene cover attaches underneath frame to hide cross braces.

Frame Finishes

Frames are available in semi-gloss silver or textured white powder-coat using baked on electrostatic process. Powder-coat is VOC free. (No Volatile Organic Compounds)

Glides

Non-marring nylon, 1.5" & .75" diameter. The glide matches the color of the one-piece shell. Glides are secured into tubed frame with 1" ribbed retention inserts.

Arms

Arm caps are (2"W x 8"L) nylon and match the color of the one-piece shell. Arm caps are inserted into tube arm frame and secured into frame with underneath bolt.

All frames are secured to shell with 4 bolts that fasten into metal inserts on polypropylene shell. A polypropylene cover attached underneath frame to hide cross braces.



Sustainability

All Imme products are Indoor Air Quality Gold Certified through Intertek. See full sustainability story at <https://www.kfistudios.com/Literature/Environmental>

Polypropylene

5-10% Pre-Consumer Recycled Content.

Frames

10% Pre-Consumer Recycled Content. VOC free powder-coating process.

Foam

100% Recyclable. CertiPUR-US certified - no ozone depleters, no mercury, lead, formaldehyde or phthalates. Low VOC (Volatile Organic compound) emissions for indoor air quality.

Glides/Casters

5-10% Pre-Consumer Recycled Content.

Hardware

10% Pre-Consumer Recycled Content.

Carton/Packaging

20% Pre-Consumer Recycled Content.

Transport Dolly

Dolly is constructed of 3mm steel frame and powder-coated in black. Locking casters are 2.5" nylon swivel. Handhold for easy transport. 2700 & 2701 stack 20 high on dolly.

Weight Ratings

All Imme Series are ANSI-BIFMA up to 300 lbs.



